

All★ Star Home - Building Checklist

Complete ALL sections below. **PLEASE PRINT.**

Submit this checklist along with a completed copy of the All-Star Home Bonus Incentive form.

| | | | | |
|-----------------------|-------|------------------------------------|-----------------|--|
| Last Name (Homeowner) | | Address (Qualifying All-Star Home) | | |
| City | State | Zip | Completion Date | |

Type of Construction:

1. New Construction
 2. Efficient Upgrade

| |
|-----------------|
| House Age (yrs) |
|-----------------|

Enter installed insulation R-values for the following components that exist in the home. **If a component does not apply, enter NA.**

| BUILDING COMPONENT | DESCRIPTION/REQUIREMENTS | Minimum Insulation R-value | Installed R-value | |
|--------------------|-----------------------------|--|-------------------|----|
| WALLS | Above Grade | Basement walls more than 50% above grade and the box sill of basement must also meet this requirement. | R-21 | |
| | Below Grade | Basement walls more than 50% below grade. | R-10 | |
| | Crawlspace Wall | Required for closed, non-vented crawlspaces. | R-20 | |
| CEILINGS | All Ceiling Types | | R-38 | |
| FLOORS | Basement (non-heated floor) | Floor at least 4 feet below grade, otherwise treat as a Slab. For walkout basements see Walkout Slab. | None | NA |
| | Basement (heated floors) | Insulation required under floor. For walkout basements see Walkout Slab. | R-10 | |
| | Slab | Floors less than 4 feet below grade. Insulation must cover face of slab with rigid foam that extends 4 feet below grade (a combination of vertical and horizontal distance can be used to meet requirement). | R-10 | |
| | Walkout Slab | The edge of floor slab (walkout side) must be insulated with rigid foam extending 4 feet below grade (a combination of vertical and horizontal distance can be used to meet requirement); remaining floor area must still meet requirements for Basement floors. | R-10 | |
| | Floor over Crawlspace | Required for open, non-vented crawlspaces. | R-30 | |

WINDOWS (Check below to verify requirements are met; provide window information)

- Must be low-E windows and meet Energy Star requirements with a U-value of 0.35 or less. At time of installation, windows should display the Energy Star label or NFRC (National Fenestration Rating Council) label showing the U-value.

Window Brand and Product Line: _____

Window Description: (example: vertical slider) _____

BUILDING LEAKAGE (Check measure used to to minimize infiltration of outdoor air)

- Exterior house wrap with all seams taped (eg. Tyvek paper)
 Exterior rigid board insulation (extruded polystyrene or urethane sheathing) with all seams taped
 Other (subject to approval). Describe: _____

Builder Information:

Homeowner or Builder Notes:

| | | |
|---------------|-------|----------|
| Business Name | | |
| Address | | |
| City | State | Zip Code |

BUILDER AGREEMENT (Signature Required)

I agree that all of the above information is true and that it represents the installed measures for the home located at the address shown. I understand that the Cooperative reserves the right to inspect the home to verify this information before issuing any rebates to the member.

Builder Signature

Date